

Spreader settings

ACCUPRO° 360ST

Settings for **Single Pass (SP)** and **Double Pass (DP)** applications

			Setting to deliver g/m²										
Product	SmartSpread™ setting	Spread width		5 g/m²	10 g/m²	15 g/m²	20 g/m²	25 g/m²	30 g/m²	35 g/m²	40 g/m²	45 g/m²	50 g/m²
Greenmaster Pro-Lite *	F	3,2 m	SP			10	11	11 ½	12 ½	13	13 ½	14 ½	15
Autumn		,	DP				9	9 1/2	10	10 ½	11		11 ½
Greenmaster Pro-Lite * Autumn MG	I	3,5 m	SP DP				9 ½ 7 ½	10 8	11 8 ½	11 ½ 9	12 9 ½	12 1/2	13 10
Greenmaster Pro-Lite *			SP			10	11	12	12 ½	13 ½	14	14 ½	15
Cold Start	G	3,5 m	DP			10	9	9 1/2	10	10 ½	11	11 1/2	12
Greenmaster Pro-Lite *			SP			9	9 1/2	10 ½	11	11 ½	12 ½	13	14
Double K CalMag	G	3,2 m	DP				8	8 1/2	9		9 1/2	10	10 ½
Greenmaster Pro-Lite *	G	3,2 m	SP			9 ½	10 ½	11 ½	12 ½	13	14	15	15 ½
Invigorator			DP				8 1/2	9	9 ½	10	10 ½	11	11 ½
Greenmaster Pro-Lite *	F	3,0 m	SP			9	10	10 ½	11 ½	12 ½	13	13 ½	14 ½
Invigorator Plus			DP				8	8 1/2	9	9 1/2	10	10 ½	11
Greenmaster Pro-Lite *	G	0.4 ===	SP			8	9 1/2	10 ½	11 ½	12	13	14	15
NK	G	3,4 m	DP				7	7 ½	8	9	9 ½	10	10 ½
Greenmaster Pro-Lite *	G	3 m	SP			8 ½	9 1/2	10	11	12	12 ½	13	14
Spring and Summer	Ü	3 111	DP				7	8	8 1/2	9	9 ½		10
Greenmaster Pro-Lite *	G	3,5 m	SP			9	10	11	11 ½	12 ½	13	13 ½	14 ½
Turf Tonic	G	3,3 111	DP				7 1/2	8 1/2	9	9 1/2	10	10 ½	11
Gronamic Golf	G	4 m	SP				12 ½	14	15 ½	17 ½	19 ½	21 ½	24 ½
Oronanne don	Ü		DP				9	9 1/2	10 ½	11 ½	12 ½	13	14
Gronamic Sport	G	3,5 m	SP				13	14	14 ½	16	17	18 ½	21
	G		DP				11	11 ½	12	12 ½	13	13 ½	14
Landscaper Pro	Н	3,5 m	SP							11 ½			
Triple Action		-,-	DP							9			
Landscaper Pro Spring & Summer /	Н	4,2 m	SP				12	13	14	15	16	17	18
Autumn & Winter	17	4 ,∠ III	DP				10	10 ½	11	11 ½	12	12 ½	13

^{*} Greenmaster Pro-Lite and Sierraform GT settings are listed separately due to variations in product density across different analyses.

The spreader settings are guidelines only. The spreader should be calibrated prior to application to ensure accuracy. The spreader settings are based on a walking speed of 5 km/hour. Walking faster or slower than 5 km/hour will alter the spread width and application rate. Exact rates are dependent upon the spreader itself and the accuracy of the person operating it.

For the latest spreader settings, please refer to the product page on the ICL website.





Spreader settings

ACCUPRO° 360ST

Settings for **Single Pass (SP)** and **Double Pass (DP)** applications

			Setting to deliver g/m ²										
Product	SmartSpread™ setting	Spread width		5 g/m²	10 g/m²	15 g/m²	20 g/m²	25 g/m²	30 g/m²	35 g/m²	40 g/m²	45 g/m²	50 g/m²
ProTurf	Н	4,2 m	SP DP				12 10	13 10 ½	14 11	15 11 ½	16 12	17 12 ½	18 13
			SP				10	10 72	16	17	18 1/2	20 1/2	23
Sierrablen	С	4,5 m	DP						12 ½	13	13 ½	14	15
Sierrablen Mini	F	3,5 m	SP				9	10	11 ½	12 ½	14	15 ½	16 ½
	·	-,	DP						8 1/2	9	9 1/2	10	10 ½
Sierrablen Plus	F	4 m	SP DP					11 ½ 9	12 ½ 9 ½	13 ½ 10	14 ½ 10 ½	15 ½ 11	16 ½ 11 ½
			SP					10 ½	11 1/2	12	10 72	13 ½	14 1/2
Sierrablen Plus Pearl (CRF formulations)	F	3,5 m	DP					.0 / 2	9	9 1/2	10	10 ½	11
Sierrablen Plus Pearl	Е	4 m	SP				11	12	13	14	15	16	17
(Turf Starter 5-28-0)		4 111	DP				8 1/2	9 1/2	10	10 ½	11	11 ½	12
Sierraform GT *	ı	3,0 m	SP			9 ½	10 ½	11	12	12 ½	13	14	14 ½
All Season		,	DP			_	8 1/2	9	9 1/2	10	10 ½		11
Sierraform GT * Anti-Stress	I	3,0 m	SP DP			9	9 ½ 8	10 ½ 8 ½	11 9	11 ½	12 ½ 9 ½	13 10	13 ½ 10 ½
Sierraform GT *			SP			9	9 1/2	10 1/2	11	11 ½	12 1/2	13	13 ½
K-Step	F	3,5 m	DP			-	8	8 1/2	9		9 1/2	10	10 ½
Sierraform GT *		4,0 m	SP			11	12	13	14	15	16	17	17 ½
Momentum	ı	4,0 111	DP				9 ½	10 ½	11	11 ½	12	12 ½	13
Sierraform GT *	1	3,0 m	SP			10	11	12	12 ½	13 ½	14	14 ½	15 ½
NK		-,	DP				9	9 ½	10	10 ½	11	11 1/2	12
Sierraform GT Preseeder	I	3,7 m	SP DP			11	12	13	14	15 11 ½	16	16 ½	17 ½
*			SP			10	8 ½ 11	9 ½ 12	11 12 ½	13 ½	12 14	12 ½ 14 ½	13 15 ½
Sierraform GT Spring Start	I	3,0 m	DP			10	9	9 1/2	10	10 ½	11	11 1/2	12
Sierraform GT *	F	2.5	SP			9 ½	10	11	11 ½	12	13	13 ½	14
Spring & Summer CalMag	F	3,5 m	DP				8 ½	9	9 1/2	10		10 ½	11

^{*} Greenmaster Pro-Lite and Sierraform GT settings are listed separately due to variations in product density across different analyses.

The spreader settings are guidelines only. The spreader should be calibrated prior to application to ensure accuracy. The spreader settings are based on a walking speed of 5 km/hour. Walking faster or slower than 5 km/hour will alter the spread width and application rate. Exact rates are dependent upon the spreader itself and the accuracy of the person operating it.

For the latest spreader settings, please refer to the product page on the ICL website.





Spreader settings

ACCUPRO° 360ST

Settings for **Single Pass (SP)** and **Double Pass (DP)** applications

			Setting to deliver g/m ²										
Product	SmartSpread™ setting	Spread width		5 g/m²	10 g/m²	15 g/m²	20 g/m²	25 g/m²	30 g/m²	35 g/m²	40 g/m²	45 g/m²	50 g/m²
Sportsmaster	G	4 m	SP DP				9 ½ 6 ½	10 ½ 7 ½	11 ½ 8	12 ½ 8 ½	13 ½ 9 ½	14 ½ 10	15 ½ 10 ½
Sportsmaster Renovator Pro	Н	3,5 m	SP DP							11 ½ 9			
Sportsmaster Cleanrun Pro	Н	3,5 m	SP DP							11 ½ 9			
Sportsmaster Base	I	4 m	SP DP				8 ½ 6 ½	9 ½ 7	10 ½ 7 ½	11 ½ 8	12 ½ 8 ½	13 ½ 9	15 9 ½
Sportsmaster CRF	С	4 m	SP DP						17 14	18 14 ½	19 ½ 15	21 ½ 15 ½	16
Sportsmaster CRF Mini	н	4 m	SP DP				12 9	13 10	14 10 ½	15 11	15 ½ 12	16 ½ 12 ½	17 ½ 13
STEP Hi Mag	G	4 m	SP DP	8 7 ½	9 8	10 8 ½							

The spreader settings are guidelines only. The spreader should be calibrated prior to application to ensure accuracy. The spreader settings are based on a walking speed of 5 km/hour. Walking faster or slower than 5 km/hour will alter the spread width and application rate. Exact rates are dependent upon the spreader itself and the accuracy of the person operating it.



